



Husqvarna®



Husqvarna FS 4600

This rear pivot saw is easy to maneuver when making multiple direction changes on the job. The addition of the optional 3-speed gearbox makes the saw more efficient by enabling different diameter blades to operate at their ideal performance level.

Features Husqvarna FS 4600

■ Gas-powered self-propelled saw has a low noise enclosed design. 48 hp Hyundai water-cooled engine. Available in rear pivot only for maneuverability in road repair and service work. Heavy-duty steel frame. Fully enclosed differential. Control panel is conveniently placed for easy operation. Direct spindle drive or 3-speed gearbox for optimum cutting performance. Catalytic muffler standard.

TECHNICAL DATA	
Motor manufacturer	Hyundai
Max output (As rated by the engine manufacturer)	35,79 kW / 48 hp
Fuel tank volume	22,71 lit
Starter	Electric
Engine cooling	Liquid/Air
Diamond blade, max	762 mm
Max cutting depth	304,8 mm
Power at blade shaft	26,1 kW
Blade shaft diameter	36,58 mm
Blade flange	101,6 mm
Arbor size	25,4 mm
Axle front	25,4 mm
Rear axle type	3-bolt hub mount
Rear axle diameter	25,4 mm
Transmission type	Hydrostatic drive
Handle bars	Multi position
Primary wheel size	Outside diameter: 152,4 Wheel width: 50,8 Inner bore: 25,4 mm
Secondary wheel size	Outside diameter: 254 Wheel width: 76,2 Inner bore: 25,4 mm
Weight	535,25 kg



Johnstone Brothers Equipment Corp.
905.796.0636