



Husqvarna FS 627

Ideal for medium to small service and repair jobs when cutting concrete or asphalt.

Features Husqvarna FS 627

- Husqvarna’s floor saws are robust, well designed and easy to use thanks to features as protective cage, lift bail and cutting depth indicator.
- Patent-pending raise/lower assist system, using gas spring.
- Raise/lower assist system Fully enclosed transmission. Lift bail is standard on all models. Dual arbors allow the blade to be mounted on either end of the bladeshaft for right or left cutting.

TECHNICAL DATA	
Motor manufacturer	Kohler
Motor spec	CH740-0001
Max output (As rated by the engine manufacturer)	20 kW / 27 hp
Cylinders	2
Number of strokes	4-stroke engine
Cylinder displacement	721,03 cm ³
Cylinder bore	83,82 mm
Cylinder stroke	67,06 mm
Fuel tank volume	19,87 lit
Starter	Electric
Engine cooling	Air
Number of belts	4
Oil capacity, l	1,8 lit
Diamond blade, max	508 mm
Max cutting depth	193,68 mm
Blade depth control	Hydraulic
Blade shaft diameter	36,51 mm
Blade flange	102 mm
Blade shaft RPM	2400 rpm
Arbor size	25,4 mm
Axle front	25,4 mm
Rear axle diameter	25,4 mm
Transmission type	Hydrostatic
Transmission speed	0-60,96 m/min
Handle bars	Multi position
Primary wheel size	Outside diameter: 152,4 Wheel width: 0 Inner bore: 0 mm
Secondary wheel size	Outside diameter: 254 Wheel width: 0 Inner bore: 0 mm
Blade guard type	Slip-on
Weight	295 kg
Weight incl. packaging	327,95 kg
Product size, LxWxH	1003x647x990 mm



Johnstone Brothers Equipment Corp.
905.796.0636