



## Husqvarna K 3000 Cut-n-Break

*Our Cut-n-Break method is the natural choice when you need to cut deep but want a machine with low tool and maintenance costs. The K 3000 Cut-N-Break enables you to cut as deep as 16" from one side. Suitable for flush cutting close to walls and floors as well as for smaller jobs like window openings where you want to avoid overcutting at the corners.*




### **COST-EFFICIENT CUTTING METHOD**

With the unique cut-n-break method you can work your way through the material step-by step at a low tool cost.



### **EXCEPTIONAL CUTTING DEPTH**

The long body and double cutting blades allow you to make cuts up to 16" deep.



### **PERFECT FOR FLUSH CUTTING**

The adjustable blade guard allows close cutting to walls and floors.



### **ERGONOMICALLY DESIGNED REAR HANDLE**

The convenient design of the rear handle makes operation easier.

## Features Husqvarna K 3000 Cut-n-Break

- Twin blades, with a very stable core and cutting performance are delivered with the machine.
- A powerful electric cutter for both indoor and outdoor use.
- The blade on all of our electric cutters rotates forward, cutting into the material efficiently, minimizing the risk of sticking and kickbacks.
- The advanced electronic overload protection varies the rotation speed to warn of approaching overload.
- Provides starting with normal, slow acting fuses.
- The water adjustment gives efficient dust management and makes operation easier and more efficient.

| TECHNICAL DATA                        |                      |
|---------------------------------------|----------------------|
| Engine                                | Electric 120V        |
| Voltage                               | 230 / 120 / 110V     |
| Rated current, A                      | 12/15/20 A           |
| Power                                 | 1800 W               |
| Rated input                           | 2700/1800/2200 W     |
| Blade diameter                        | 230 mm               |
| Max cutting depth                     | 400 mm               |
| Weight (excl. cutting equipment)      | 8,9 kg               |
| Weight incl. cutting equipment        | 10,4 kg              |
| Vibrations front handle               | 3,2 m/s <sup>2</sup> |
| Vibrations rear handle                | 3,4 m/s <sup>2</sup> |
| Sound power level, guaranteed (LWA)   | 109 dB(A)            |
| Sound pressure level at operators ear | 95 dB(A)             |



**Johnstone Brothers Equipment Corp.**  
*905.796.0636*