



## Husqvarna K 3600 MK II

*The eccentric rim drive system of hydraulic power cutter K 3600 MK II provides a 10" cutting dept with a 14" blade. It's suitable for a wide variety of applications, such as correcting door and window openings and cutting pipe in installation jobs. It's ideal for working indoors due to no exhaust fumes and low noise levels.*



### DEEP CUTTING

Thanks to the peripheral drive you can cut far deeper than with a traditional power cutter. The cutting depth of 10" is sufficient to cut through a normal wall from one side only.



### NO FUMES AND LOW NOISE LEVELS

Running a hydraulic cutter means you avoid fumes and high noise levels, so they are ideal for both indoor and outdoor jobs.



### LIGHT WITH HIGH POWER

Hydraulics is an excellent way to transfer high power without the cutter becoming heavy.



### ADJUSTABLE FRONT HANDLE

Facilitates maneuverable cutting

## Features Husqvarna K 3600 MK II

- The water adjustment gives efficient dust management and makes operation easier and more efficient.

TECHNICAL DATA	
Power output	4,3 kW
Hydraulic flow, max	40 l/min
Hydraulic pressure	140 bar
Max cutting depth	270 mm
Blade diameter	370 mm
Weight (excl. cutting equipment)	8,3 kg
Vibrations front handle	4,3 m/s <sup>2</sup>
Vibrations rear handle	6 m/s <sup>2</sup>
Sound power level, guaranteed (LWA)	111 dB(A)
Sound pressure level at operators ear	99 dB(A)



**Johnstone Brothers Equipment Corp.**

**905.796.0636**