




## Husqvarna K 6500 Chain

*K 6500 Chain is equipped with high frequency PRIME™ technology, making it a very powerful electric chain cutter. The high power output, well-balanced body and low vibrations make this machine very efficient and easy to use. With K 6500 Chain it is possible to cut 450 mm deep from one side, making this machine a great complement to wall saws to avoid overcutting at corners. It is also ideal for cutting irregular or small openings (as small as 11x11 cm). The PRIME™ product range enables you to combine the system that is most efficient for your business. K 6500 can be used with either PP 65 or PP 220 as a power source. Expand the system as your needs develop.*



### DEEP CUTTING

Possible to cut 450 mm from one side.



### IMPRESSIVE POWER

High power output on both 3-phase (5.5 kW) and 1-phase (3 kW) at 220 - 240 V /180-480 V



### ERGONOMIC DESIGN

The ergonomic design with low system weight and well balanced body with optimally positioned handles minimize the strain on your body.



### FLEXIBLE POWER SETUP

Operates with both 3- and 1-phase power.

## Features Husqvarna K 6500 Chain

- This machine is controlled by a power pack with built-in intelligence that communicates with the machine motor to ensure optimal power and rpm for each cutting job.
- Our anti-vibration system reduces vibrations in the cutter handles, so they are more comfortable to hold and can be used for longer periods. To provide the user a comfortable operating position and to reduce strain, the distance between the handles is large. The handles and the short engine body mean the user always stands close to the machine, for easier handling and control.
- Overload protection by LED indicator
- Easy tension of chain
- A powerful electric cutter for both indoor and outdoor use.

TECHNICAL DATA	
Power	5500 W
Bar length	400 mm
Max cutting depth	450 mm
Weight (excl. cutting equipment)	9,1 kg
Vibrations front handle	2,7 m/s <sup>2</sup>
Vibrations rear handle	2,1 m/s <sup>2</sup>
Sound power level, guaranteed (LWA)	112 dB(A)
Sound pressure level at operators ear	99 dB(A)



**Johnstone Brothers Equipment Corp.**  
**905.796.0636**