



Husqvarna K 6500 Ring

Husqvarna K 6500 Ring is equipped with high frequency PRIME™ technology, making it our most powerful electric ring cutter ever. The high power output, well-balanced body and low vibration levels make this machine very efficient and easy to use. The PRIME™ product range enables you to combine the system that is most efficient for your business. The K 6500 can be used with either the PP 65 or the PP 220 as a power source. Expand the system as your needs develop.



DEEP CUTTING

Thanks to the peripheral drive you can cut far deeper than with a traditional power cutter. The cutting depth of 10" is sufficient to cut through a normal wall from one side only.



IMPRESSIVE POWER

High power output on both 3-phase (5.5 kW) and 1-phase (3 kW) at 220 - 240 V /180-480 V



EXCEPTIONALLY LOW VIBRATIONS

Vibrations below 2.5 m/s² in the cutter handles for more comfort and longer operation periods.



ERGONOMIC DESIGN

The ergonomic design with low system weight and well balanced body with optimally positioned handles minimize the strain on your body.

Features Husqvarna K 6500 Ring

- Overload protection by LED indicator
- This machine is controlled by a power pack with built-in intelligence that communicates with the machine motor to ensure optimal power and rpm for each cutting job.
- Operates with both 3- and 1-phase power.
- Wet cutting is supported by easily adjustable water flow during operation. The water flow starts first when the trigger lock-out is activated.
- The blade on all of our electric cutters rotates forward, cutting into the material efficiently, minimizing the risk of sticking and kickbacks.
- A powerful electric cutter for both indoor and outdoor use.
- The On/Off water trigger supports wet cutting, with easily adjustable water flow during operation. The water flow starts first when the trigger lock-out is activated.

| TECHNICAL DATA | |
|---------------------------------------|----------------------|
| Power | 5500 W |
| Blade diameter | 370 mm |
| Max cutting depth | 270 mm |
| Weight (excl. cutting equipment) | 13,1 kg |
| Vibrations front handle | 2,4 m/s ² |
| Vibrations rear handle | 1,5 m/s ² |
| Sound power level, guaranteed (LWA) | 111 dB(A) |
| Sound pressure level at operators ear | 99 dB(A) |



Johnstone Brothers Equipment Corp.
905.796.0636