



## Husqvarna K 760 Rescue

*Our compact and lightest rescue cutter is specially developed for rescue and clearing work. The chromium-plated blade guard is designed to be visible in smoke and water spray, and the digital ignition system provides a reliable and quick start in any emergency situation. Used and trusted by fire services around the world.*



### **CHROMIUM-PLATED BLADE GUARD**

For high visibility in smoke and water spray, which enhances control of the cutter.



### **SPECIALLY DESIGNED STARTER HANDLE**

Specially designed starter handle, with room for heavy gloves.



### **ADJUSTABLE CARRY STRAP**

Adjustable carry strap allows full freedom of movement.



### **OPTIMIZED ENGINE PERFORMANCE**

Optimized engine performance through efficient cylinder design, digital ignition system and X-Torq® engine technology.

## Features Husqvarna K 760 Rescue

- Easy to start
- Vibrations below 2.5 m/s<sup>2</sup> in the cutter handles for more comfort and longer operation periods.
- Light and powerful
- Long service intervals
- The only time the filter needs to be checked and changed is if you experience lack of power.
- High power with less fuel
- Fits multiple blade bushings
- Our X-Torq® engine produces less emissions, has lower fuel consumption and results in more power.
- Blade retarder
- Patented, dust sealed starter unit with a sealed return spring and pulley bearing. DuraStarter™ also includes a starter cord with greatly increased durability. This makes the starter virtually maintenance free, further enhancing the reliability of our cutters.
- Reduced wear thanks to the drive belt with fully sealed transmission, which keeps out the cutting dust.
- Our virtually maintenance free starter, thanks to the dust-sealed starter and the durable starter cord.
- Provides better transmission of power, less frequent re-tensioning and extended service intervals.
- The drive belt with fully sealed transmission keeps out cutting dust for reduced wear and allows close cutting to walls and floor.
- Our two-step filtration system with centrifugal cleaning and a single paper filter increases product life and extends service intervals.
- Our built-in automatic filter compensation maintains high power during the air filter life time.
- EasyStart ensures easier starting by reducing the compression in the cylinder.

TECHNICAL DATA	
Engine	Air-cooled 2 stroke engine
Cylinder displacement	73,5 cm <sup>3</sup>
Power output	3,7 kW
Fuel tank volume	0,9 lit
Idling speed	2700 rpm
Vibrations front handle	2,4 m/s <sup>2</sup>
Vibrations rear handle	2,4 m/s <sup>2</sup>
Sound pressure level at operators ear	101 dB(A)
Sound power level, guaranteed (LWA)	115 dB(A)
Blade diameter	300 mm
Max cutting depth	100 mm
Arbor Size	20 mm
Weight (excl. cutting equipment)	9,6 kg



**Johnstone Brothers Equipment Corp.**  
905.796.0636