



Husqvarna K 970 Rescue

Our most powerful rescue cutter is specially developed for rescue and clearing work. The magnesium blade guard is designed to be visible in smoke and water spray, and the digital ignition system provides a reliable and quick start in any emergency situation. Used and trusted by fire services around the world.



EASY AND OPTIMAL BELT TENSIONING

The semi-automatic SmartTension minimises the risk of under- and over-tensioning.



MAGNESIUM BLADE GUARD

With decreased weight and reflective decals for high visibility in smoke and water spray, which enhances control of the cutter.



SPECIALLY DESIGNED STARTER HANDLE

Specially designed starter handle, with room for heavy gloves.



STURDY AND RELIABLE

Less sensitive to outdoor conditions and fuel variations, thanks to the cylinder design and muffer with integrated heat deflector.

Features Husqvarna K 970 Rescue

- Adjustable carry strap
- Optimal ignition timing makes the power cutter start easily in any situation.
- Long service intervals
- Light and powerful
- The only time the filter needs to be checked and changed is if you experience lack of power.
- High power with less fuel
- Our two-step filtration system with centrifugal cleaning and a single paper filter increases product life and extends service intervals.
- Reduced wear thanks to the drive belt with fully sealed transmission, which keeps out the cutting dust.
- Blade retarder
- Our X-Torq® engine produces less emissions, has lower fuel consumption and results in more power.
- Our built-in automatic filter compensation maintains high power during the air filter life time.
- Patented, dust sealed starter unit with a sealed return spring and pulley bearing. DuraStarter™ also includes a starter cord with greatly increased durability. This makes the starter virtually maintenance free, further enhancing the reliability of our cutters.
- The cutting arm is reversible which lets you cut closer to walls or the ground. The drive belt has a fully sealed transmission. This keeps out cutting dust etc, reducing wear.
- Our anti-vibration system reduces vibrations in the cutter handles, so they are more comfortable to hold and can be used for longer periods. To provide the user a comfortable operating position and to reduce strain, the distance between the handles is large. The handles and the short engine body mean the user always stands close to the machine, for easier handling and control.

TECHNICAL DATA

Engine	Air-cooled 2 stroke engine
Cylinder displacement	93,6 cm ³
Power output	4,8 kW
Fuel tank volume	1 lit
Idling speed	2700 rpm
Vibrations front handle	3,8 m/s ²
Vibrations rear handle	4,2 m/s ²
Sound pressure level at operators ear	104 dB(A)
Sound power level, guaranteed (LWA)	115 dB(A)
Blade diameter	350 mm
Max cutting depth	125 mm
Combined bushing diameter	20/25,4 mm
Weight (excl. cutting equipment)	11 kg



Johnstone Brothers Equipment Corp.
905.796.0636