



Infrared Asphalt Heater KM 2-18X

KM 2-18X 3'6"x6'6" Infrared Asphalt Heater

Pavers Solutions

The lightweight KM2-18X is easily moved to service areas previously inaccessible. The fully self contained infrared unit is a workhorse and will provide many hours of repairs using two 30 pound cylinders of propane. This is the perfect machine for new pavement fixes and utility cut repairs.

The KM2-18X offers the operator an option to use either a single 3'-6" x 3'-3" zone or dual 3'-6" x 6'-6" zones totaling 22.75 square feet of infrared heat. This unit also works well for thermoplastic template applications.

Used for:

- Pavers
- Cold Seams
- Rough Spots
- Bird Bath Repairs
- Roller Marks

KM 2-18X Specifications

Transit dimensions:	4' 10" W x 6' 6" L x 44" H, includes casters
Heating dimensions:	3' 6" W x 6' 6" L
Weight:	410 lb (185 kg)
Heating zones:	Two (2) independent, each 3' 6" (106 cm) x 3' 3" (99 cm)
Heating element:	Infrared radiant, 1" (2.54 cm) refractory ceramic blanket
Fuel:	Propane
Propane:	Two (2), 30 lb. cylinders
Fuel Consumption:	12 lbs./ hour, cycled heating
BTU output:	300,000 BTU
Blower:	12 Volt DC powered
Battery:	12 Volt, deep cycle marine gel
Safety:	Manual initiated emergency stop control
Operating control:	Keyed ON/OFF power switch, Momentary ON/OFF switch, 10 Minute auto time-out, Automatic heat cycling sequence ON/OFF push button zone control
Ignition:	Automatic electronic pilot light

Specifications subject to change without notice



Johnstone Brothers Equipment Corp.
905.796.0636