

## 2-Ton Trailer Mounted Asphalt Hot Box KM 4000T

## **KM 4000T 2-Ton Trailer Mounted Asphalt Hot Boxes**

Two ton asphalt capacity trailer unit. Asphalt hotbox reclaimer allows asphalt to be maintained at working temperature for up to 3 days.

Insulated, gravity feed shovel port

Dual shovel/took rack. Automatic LP changeover regulator. Thermostatically controlled heat with 100% safety shut down.

Reclaimer: When new asphalt is unavailable, stockpiled or used material can be used. Within 12 hours the hard, cold chunked asphalt is reclaimed to hot mix.

## **KM 4000T Specifications**

Capacity of asphalt:	4,000 lbs. of material
Heating element:	58,000 BTU propane
	105,000 BTU optional diesel burner
Fuel supply:	Two (2) 30 lb. cylinders
	25 gallon fuel tank with #2 diesel fuel (option)
Pilot:	Electronic fuel ignition with 100%
	safety shut down capability
Filling door:	Single high temperature insulated lid with
	adjustable lock down latches for secure loads.
	Includes gas spring open assist, single
	cantilever opening handle
Shovel port:	Single insulated door on sliding track,
	17" W x 17" H
Dimensions:	156" L x 96" W x 70" H
Construction:	All welded steel, triple welded construction 16
	gauge skin, 12 gauge asphalt compartment
Capacity (trailer):	7,000 lbs. GVWR
Axle:	Single 7,000 lb. TORFLEX, standard electric brakes
Tires and wheels:	3,520 lbs. LR E (each)
Weight:	2,180 lbs. (including optional tack tank, solvent
	tank and torch)

Specifications subject to change without notice





