



1-305

Patch and Go.



Keep things smooth with Multiquip's "one-person patch crew" - the V305EH walk behind roller. Designed to meet operator expectations for easy steering and transport, the V305 is the ideal option for small repair and maintenance jobs.



- 1 **Reliable Honda GX340** engine for easy starting and quiet operation.
- 2 **Maintenance free** vibratory assembly requires no greasing to reduce service time.
- 3 **Elongated handle** provides leverage for increased maneuverability and three height adjustments enhance operator comfort.
- 4 **Three water flow adjustment** settings allow for even water distribution to the drum.
- 5 **Hour/Tachometer** simplifies service and tracks maintenance intervals.
- 6 **Swing away hood** requires no tools to access internal components.
- 7 **Adjustable transport hooks** are easily changed to meet truck height requirements.
- 8 **Central lifting eye** for balanced lifting.
- 9 **Stabilizing rollers** help maintain operator balance.
- 10 **29" wide steel drum** with beveled edges helps prevent asphalt marring.
- 11 **Hydrostatic drive system** offers variable speed control, smooth acceleration and braking.

Specifications	V305EH
<b>Operating Weight w/o Water</b> - lbs (kg)	1,168 (530)
<b>Overall Length</b> - in (mm)	88.5 (2,248)
<b>Overall Width</b> - in (mm)	35 (890)
<b>Overall Height</b> - in (mm)	86.5 (2,197)
<b>Drum Width</b> - in (mm)	29 (737)
<b>Drum Diameter</b> - in (mm)	22 (559)
<b>Curb Clearance Right</b> - in (mm)	16.5 (419)
<b>Curb Clearance Left</b> - in (mm)	4.5 (114)
<b>Wall Clearance Right</b> - in (mm)	0.75 (19)
<b>Wall Clearance Left</b> - in (mm)	4.5 (114)
<b>Centrifugal Force</b> - lbf (kn)	3,800 (16.9)
<b>Frequency</b> - vpm (Hz)	4,200 (70)
<b>Travel Speed Forward</b> - mph (kmh)	2.5 (4)
<b>Travel Speed Reverse</b> - mph (kmh)	1.7 (2.7)
<b>Gradeability Maximum</b> - (%)	10
<b>Engine</b>	
<b>Engine Manufacturer</b>	Honda GX340
<b>Operating Speed</b> - (rpm)	3,100
<b>Horse Power Rating</b> - hp (kw)	10.7 (8)
<b>Fuel Tank Capacity</b> - gal (l)	1.6 (6.1)
<b>Water System</b>	
<b>Water Tank Capacity</b> - gal (l)	7 (26.5)
<b>Water Tank</b>	Plastic
<b>Water Release Control</b>	On Handle
<b>Water Flow</b>	3 Detents
<b>Service Features</b>	
<b>Vibratory Assembly</b>	Maintenance Free
<b>Electronic Display</b>	Hour/Tachometer



Spring loaded scraper bar folds up for easy change out and cleanup.



Patent pending plastic water tank eliminates water flow obstructions from rust build-up.



Multi-functional handle controls forward and reverse travel, water flow to the drum, vibration and the emergency stop feature.

Your Multiquip dealer is:



**Johnstone Brothers Equipment Corp.**  
905.796.0636

**WARRANTY:**

V305 Vibratory roller- 1 year parts and labor. Contact Multiquip for complete warranty information.  
Honda GX340- 3 years. Please consult with Honda for warranty details and updates.

